

**B.E.G.****LUXOMAT<sup>®</sup> net**

## PBM-KNX-DX-4W

Prod.No. 93365 EAN: 4007529933655

- Voltage: via KNX BUS
- Dimensions: 38 x 41 x 12 mm
- Typ. power input: 9.5 mA (typ.) (I<sub>max</sub> parameterisable 12.5 mA or 20 mA)

### Order data

Designation	Colour	Art.No
PBM-KNX-DX-4W		93365

## Technical data

Voltage:	via KNX BUS
Dimensions:	38 x 41 x 12 mm
Typ. power input:	9.5 mA (typ.) (I <sub>max</sub> parameterisable 12.5 mA or 20 mA)
Degree / class of protection:	IP20 / Class III
Ambient temperature:	-5 °C to +45 °C
Display elements:	Programming LED
KNX TP 256:	Yes
Connections and wires:	plug board: 8 pin Prefabricated connecting wires (extendable to a total of max. 5 m)
LED connector:	I <sub>max</sub> 3.6 mA const. (PWM) LED 3.5 V / 4 mA

## Product information

Binary input or output device (push button interface) for pattress boxes (60 mm)

There are four channels available. Each can either be used as input for a potential-free push-button or switch contact or as binary output for switching a control lamp.

User-friendly ETS interface

The following functions are possible:

- Switching
- Forced operation
- Percentage
- Sequencer
- HVAC mode
- Dimming
- Blinds control
- Scene
- Edge function
- Counter

Settings ex ETS 4 for integration in KNX systems

The product database for import into the ETS database can be downloaded from the B.E.G. homepage.



