



## LK-TP/KNXs REG

Prod.No. 90410 EAN: 4007529904105

KNX TP Line coupler in a compact design. It connects two KNX bus segments via twisted pair

KNX Secure ready

extended filter table for main group 0 to 31

### Order data

| Designation    | Colour | Art.No |
|----------------|--------|--------|
| LK-TP/KNXs REG | -      | 90410  |

## Technical data

|                               |                                  |
|-------------------------------|----------------------------------|
| Voltage:                      | via KNX BUS                      |
| Dimensions:                   | 90 x 18 x 55 mm (1 TE)           |
| Typ. power input:             | 10 mA typical                    |
| Degree / class of protection: | IP20 / Class III                 |
| Ambient temperature:          | -5 °C to +45 °C                  |
| Housing:                      | polycarbonate, UV-resistant (PC) |
| Material color:               | -                                |
| KNX TP 256:                   | Yes                              |
| KNX Secure:                   | Yes                              |
| Connections and wires:        | 2 x KNX bus terminal black/red   |

## Product information

KNX TP Line coupler in a compact design. It connects two KNX bus segments via twisted pair

KNX Secure ready

extended filter table for main group 0 to 31

ensures a galvanic isolation between the lines

Supports KNX long frames

Buffer for up to 2 x 50 telegrams

Security proxy and segment coupler function

The buttons on the front panel allow disabling the telegram filter for testing purposes

LEDs to indicate operating conditions as well as errors



