
B.E.G. LUXOMAT® net



SA12 - 230 / 16 / H / KNXs REG

Prod.No. 93328 EAN: 4007529933280

Switching actuator for switching loads

KNX Secure ready

Industrial quality

Order data

Designation	Colour	Art.No
SA12 - 230 / 16 / H / KNXs REG	-	93328

Technical data

Voltage:	via KNX BUS
Dimensions:	90 x 216 x 64 mm (12 TE)
Typ. power input:	5 mA typical 20 mA max.
Power consumption:	0.15 W
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-5 °C to +45 °C
Material color:	-
KNX TP 256:	Yes
KNX Secure:	Yes
Connections and wires:	KNX bus terminal black/red 0.2 ... 4.0 mm² rigid 0.25 ... 2.5 mm² fine-wired (with or without ferrule)
per channel	
Switching power:	3680 W, cos φ = 1 max. inrush current Ip (150 µs) = 600 A
Type of contact (k):	µ-contacts, dry NO contact
Outputs:	12 switching outputs

Product information

Switching actuator for switching loads

KNX Secure ready

Industrial quality

KNX rail-mounting device for mounting on a DIN rail (TH 35 according to EN 60715) for installation in the distribution board

12 independent, potential-free normally open contacts

The switching contacts are optimised for capacitive loads

operating hours counter

cycle counter

8 scene functions per channel

Extensive logic functions

Locking functions

safety features

Staircase and flashing function


Switch-on and switch-off delays


Manual switches for switching without bus tension

Powered via KNX bus

Connection of the outputs via screw terminals

The product database can be downloaded from the B.E.G. homepage or imported directly from the ETS online catalogue


216
58
44
90
6
45
9


L1
L2
L3
N
R1 R1 R2 R2 N/A R3 R3 R4 R4 R5 R5 R6 R6 N/A R7 R7 R8 R8 R9 R9 R10 R10 N/A R11 R11 R12 R12
- +
KNX
+
-
KNX